

## Hydraulic hoses

# 1 SN

### Tube

oil resisnant synthetic rubber

### Reinforcement

high tensile steel wire netting

### Cover

synthetic rubber with high abrasion, ozone, weather resistance

### Temperature

-40°C to +100°C

### Standard

DIN EN 853; SAE 100 R1S



Bestell-Nr.	DN in mm	internal Ø in mm	external Ø in mm	reinforcement Ø in mm	working pressure in bar	burst pressure in bar	min. bending radius R in mm	weight in kg/m
<b>11-04</b>	6	6,4	13,4	11,1	225	900	100	0,28
<b>11-05</b>	8	7,9	15,0	12,7	215	850	115	0,32
<b>11-06</b>	10	9,5	17,4	15,1	180	720	130	0,40
<b>11-08</b>	12	12,7	20,6	18,3	160	640	180	0,50
<b>11-10</b>	16	15,9	23,7	21,4	130	520	200	0,66
<b>11-12</b>	19	19,1	27,7	25,4	105	420	240	0,73
<b>11-16</b>	25	25,4	35,6	33,3	88	350	300	1,08
<b>11-20</b>	31	31,8	43,5	40,5	63	250	420	1,35
<b>11-24</b>	38	38,1	50,6	46,8	50	200	500	1,70

11-32	51	50,8	64,0	60,2	40	160	630	2,20
-------	----	------	------	------	----	-----	-----	------