

## Hydraulic hoses FLEXtreme (17A)

### Tube

Black smooth synthetic rubber, conductive

### Reinforcement

High tensile textile plies and helix wires embedded

### Cover

Black, smooth rubber, abrasion, oil, fuel, ozone and weather resistant

### Temperature

-40° up to 100°C



Bestell-Nr.	DN in mm	DN in inch	internal Ø in mm	Tolerance internal Ø in mm	external Ø in mm	negative pressure	working pressure	burst pressure	min. bending radius R in mm	weight in kg/m
<b>17A-12</b>	19	3/4	19	±0,8	29	-1	25	75	38	0,58
<b>17A-16</b>	25	1	25	±0,8	35	-1	20	60	50	0,75
<b>17A-20</b>	31	1 1/4	32	±1,2	42	-1	17	51	64	0,92
<b>17A-24</b>	38	1 1/2	38	±1,2	48	-1	10	30	76	1,07
<b>17A-32</b>	51	2	51	±1,6	61	-1	10	30	102	1,39
<b>17A-36</b>	60	2 3/8	60	±1,6	72	-1	10	30	120	2,10
<b>17A-40</b>	63	2 1/2	63	±1,6	75	-1	10	30	126	2,10
<b>17A-48</b>	76	3	76	±1,6	88	-1	7	20	152	2,60

<b>17A-56</b>	90	3 1/2	90	±1,6	102	-1	7	20	180	3,04
<b>17A-64</b>	102	4	102	±1,6	116	-1	7	20	204	3,41
<b>17A-80</b>	127	5	127	±1,6	143	-0,9	7	20	254	5,53
<b>17A-96</b>	152	6	152	±1,6	168	-0,9	7	20	304	6,81