Pressure fittings
BES 45°

Connection
Pipe connection for cutting ring coupling S series

Standard
ISO 8434-1

Application
TE / SN / SC / SN-K / PTFE flexible tubes

Material
Steel

Surface protection
Zinc-electroplated



Dietzel Hydraulik GmbH
Leedenstraße 10
04626 Löbichau

Tel.: +49 (36602) 140-140
E-Mail: vertrieb@dietzel-hydraulik.de

Bestell-Nr.	DN in mm	RA	min. D in mm	E±3 in mm	B±3 in mm	L±3 in mm
1.125-02-04	06	6S	3,0	20,0	51	78
1.125-03-04	06	8S	4,0	20,0	53	80
1.125-04-04	06	10S	4,0	22,0	54	81
1.125-03-05	08	8S	5,0	20,0	53	80
1.125-04-05	08	10S	5,5	22,0	53	80
1.125-05-05	08	12S	5,5	22,0	57	84
1.125-05-06	10	12S	7,0	22,0	57	87
1.125-06-06	10	14S	7,0	22,5	61	91
1.125-08-06	10	16S	7,0	31,0	74	104
1.125-06-08	12	14S	8,0	22,5	63	94
1.125-08-08	12	16S	10,0	31,0	77	108
1.125-10-08	12	20S	10,0	32,0	80	111
1.125-10-10	16	20S	13,0	32,0	81	115
1.125-12-12	19	25S	15,0	40,0	91	130
1.125-16-16	25	30S	20,0	43,0	101	147
1.125-20-20	31	38S	27,0	46,0	110	164

Dietzel Hydraulik GmbH
Leedenstraße 10
04626 Löbichau

Tel.: +49 (36602) 140-140
E-Mail: vertrieb@dietzel-hydraulik.de